
Labelbox Python API reference

Release 3.0.0-rc0

Labelbox

Oct 05, 2021

CONTENTS:

1	Client	1
2	AssetAttachment	7
3	Benchmark	9
4	BulkImportRequest	11
5	DataRow	13
6	Dataset	15
7	Label	19
8	LabelingFrontend	21
9	LabelingFrontendOptions	23
10	LabelingParameterOverride	25
11	Ontology	27
12	Organization	29
13	Project	31
14	Review	37
15	Task	39
16	User	41
17	Webhook	43
18	Exceptions	45
19	Pagination	47
20	Enums	49
	Python Module Index	51
	Index	53

CHAPTER ONE

CLIENT

```
class labelbox.client.Client(api_key=None, endpoint='https://api.labelbox.com/graphql', enable_experimental=False, app_url='https://app.labelbox.com')
```

Bases: object

A Labelbox client.

Contains info necessary for connecting to a Labelbox server (URL, authentication key). Provides functions for querying and creating top-level data objects (Projects, Datasets).

```
__init__(api_key=None, endpoint='https://api.labelbox.com/graphql', enable_experimental=False, app_url='https://app.labelbox.com')
```

Creates and initializes a Labelbox Client.

Logging is defaulted to level WARNING. To receive more verbose output to console, update *logging.level* to the appropriate level.

```
>>> logging.basicConfig(level = logging.INFO)
>>> client = Client("<APIKEY>")
```

Parameters

- **api_key** (*str*) – API key. If None, the key is obtained from the “LABELBOX_API_KEY” environment variable.
- **endpoint** (*str*) – URL of the Labelbox server to connect to.
- **enable_experimental** (*bool*) – Indicates whether or not to use experimental features
- **app_url** (*str*) – host url for all links to the web app

Raises `labelbox.exceptions.AuthenticationError` – If no *api_key* is provided as an argument or via the environment variable.

```
create_dataset(iam_integration='DEFAULT', **kwargs)
```

Creates a Dataset object on the server.

Attribute values are passed as keyword arguments.

```
>>> project = client.get_project("<project_uid>")
>>> dataset = client.create_dataset(name="<dataset_name>", projects=project)
```

Parameters

- **iam_integration** (*IAMIntegration*) – Uses the default integration. Optionally specify another integration or set as None to not use delegated access

- ****kwargs** – Keyword arguments with Dataset attribute values.

Returns A new Dataset object.

Raises `InvalidAttributeError` – If the Dataset type does not contain any of the attribute names given in kwargs.

create_model (*name*, *ontology_id*)

Creates a Model object on the server.

```
>>> model = client.create_model(<model_name>, <ontology_id>)
```

Parameters

- **name** (*string*) – Name of the model
- **ontology_id** (*string*) – ID of the related ontology

Returns A new Model object.

Raises `InvalidAttributeError` – If the Model type does not contain any of the attribute names given in kwargs.

create_project (**kwargs)

Creates a Project object on the server.

Attribute values are passed as keyword arguments.

```
>>> project = client.create_project(name="<project_name>", description="
-><project_description>")
```

Parameters ****kwargs** – Keyword arguments with Project attribute values.

Returns A new Project object.

Raises `InvalidAttributeError` – If the Project type does not contain any of the attribute names given in kwargs.

execute (*query=None*, *params=None*, *data=None*, *files=None*, *timeout=30.0*, *experimental=False*)

Sends a request to the server for the execution of the given query.

Checks the response for errors and wraps errors in appropriate `labelbox.exceptions.LabelboxError` sub-types.

Parameters

- **query** (*str*) – The query to execute.
- **params** (*dict*) – Query parameters referenced within the query.
- **data** (*str*) – json string containing the query to execute
- **files** (*dict*) – file arguments for request
- **timeout** (*float*) – Max allowed time for query execution, in seconds.

Returns dict, parsed JSON response.

Raises

- `labelbox.exceptions.AuthenticationError` – If authentication failed.
- `labelbox.exceptions.InvalidQueryError` – If *query* is not syntactically or semantically valid (checked server-side).

- `labelbox.exceptions.ApiLimitError` – If the server API limit was exceeded. See “How to import data” in the online documentation to see API limits.
 - `labelbox.exceptions.TimeoutError` – If response was not received in `timeout` seconds.
 - `labelbox.exceptions.NetworkError` – If an unknown error occurred most likely due to connection issues.
 - `labelbox.exceptions.LabelboxError` – If an unknown error of any kind occurred.
 - `ValueError` – If query and data are both None.

get_data_row (*data_row_id*)

Returns returns a single data row given the data row id

Return type *DataRow*

```
get_data_row_metadata_ontology()
```

Returns The ontology for Data Row Metadata for an organization

Return type DataRowMetadataOntology

get_dataset (*dataset_id*)

Gets a single Dataset with the given ID.

```
>>> dataset = client.get_dataset("<dataset_id>")
```

Parameters `dataset_id` (`str`) – Unique ID of the Dataset.
Returns The sought Dataset.
Raises `labelbox.exceptions.ResourceNotFoundError` – If there is no Dataset

`_datasets (where=None)`

```
>>> datasets = client.get_datasets(where=(Dataset.name == "<dataset_name>") & _
```

Parameters `where` (*Comparison, LogicalOperation or None*) – The `where`

clause for filtering.

_labeling_frontends (*when*)

```
>>> frontend = client.get_labeling_frontends(where=LabelingFrontend.name ==
```

`get_model(model_id)`

Gets a single Model with the given ID.

```
>>> model = client.get_model("<model_id>")
```

Parameters `model_id` (`str`) – Unique ID of the Model.

Returns The sought Model.

Raises `labelbox.exceptions.ResourceNotFoundError` – If there is no Model with the given ID.

`get_models(where=None)`

Fetches all the models the user has access to.

```
>>> models = client.get_models(where=(Model.name == "<model_name>"))
```

Parameters `where` (`Comparison, LogicalOperation or None`) – The `where` clause for filtering.

Returns An iterable of Models (typically a PaginatedCollection).

`get_organization()`

Gets the Organization DB object of the current user.

```
>>> organization = client.get_organization()
```

`get_project(project_id)`

Gets a single Project with the given ID.

```
>>> project = client.get_project("<project_id>")
```

Parameters `project_id` (`str`) – Unique ID of the Project.

Returns The sought Project.

Raises `labelbox.exceptions.ResourceNotFoundError` – If there is no Project with the given ID.

`get_projects(where=None)`

Fetches all the projects the user has access to.

```
>>> projects = client.get_projects(where=(Project.name == "<project_name>") &  
    ~ (Project.description == "<project_description>"))
```

Parameters `where` (`Comparison, LogicalOperation or None`) – The `where` clause for filtering.

Returns An iterable of Projects (typically a PaginatedCollection).

`get_roles()`

Returns Provides information on available roles within an organization. Roles are used for user management.

Return type Roles

get_user()

Gets the current User database object.

```
>>> user = client.get_user()
```

CHAPTER
TWO

ASSETATTACHMENT

```
class labelbox.schema.asset_attachment.AssetAttachment(client, field_values)  
Bases: labelbox.orm.db_object.DbObject
```

Asset attachment provides extra context about an asset while labeling.

attachment_type
IMAGE, VIDEO, TEXT, IMAGE_OVERLAY, or HTML

Type str

attachment_value
URL to an external file or a string of text

Type str

```
class AttachmentType(value)  
Bases: enum.Enum
```

An enumeration.

CHAPTER
THREE

BENCHMARK

```
class labelbox.schema.benchmark.Benchmark (client, field_values)  
Bases: labelbox.orm.db_object.DbObject
```

Represents a benchmark label.

The Benchmarks tool works by interspersing data to be labeled, for which there is a benchmark label, to each person labeling. These labeled data are compared against their respective benchmark and an accuracy score between 0 and 100 percent is calculated.

created_at

Type datetime

last_activity

Type datetime

average_agreement

Type float

completed_count

Type int

created_by

ToOne relationship to User

Type Relationship

reference_label

ToOne relationship to Label

Type Relationship

BULKIMPORTREQUEST

```
class labelbox.schema.bulk_import_request.BulkImportRequest (client, field_values)
Bases: labelbox.orm.db_object.DbObject
```

Represents the import job when importing annotations.

name

Type str

state

FAILED, RUNNING, or FINISHED (Refers to the whole import job)

Type Enum

input_file_url

URL to your web-hosted NDJSON file

Type str

error_file_url

NDJSON that contains error messages for failed annotations

Type str

status_file_url

NDJSON that contains status for each annotation

Type str

created_at

UTC timestamp for date BulkImportRequest was created

Type datetime

project

ToOne relationship to Project

Type Relationship

created_by

ToOne relationship to User

Type Relationship

delete() → None

Deletes the import job and also any annotations created by this import.

Returns None

property errors

Errors for each individual annotation uploaded. This is a subset of statuses

Returns List of dicts containing error messages. Empty list means there were no errors. See *BulkImportRequest.statuses* for more details.

- This information will expire after 24 hours.

property inputs

Inputs for each individual annotation uploaded. This should match the ndjson annotations that you have uploaded.

Returns Uploaded ndjson.

- This information will expire after 24 hours.

refresh() → None

Synchronizes values of all fields with the database.

property statuses

Status for each individual annotation uploaded.

Returns A status for each annotation if the upload is done running. See below table for more details

Field	Description
uuid	Specifies the annotation for the status row.
dataRow	JSON object containing the Labelbox data row ID for the annotation.
status	Indicates SUCCESS or FAILURE.
errors	An array of error messages included when status is FAILURE. Each error has a name, message and optional (key might not exist) additional_info.

- This information will expire after 24 hours.

wait_until_done(sleep_time_seconds: int = 5) → None

Blocks import job until certain conditions are met.

Blocks until the *BulkImportRequest.state* changes either to *BulkImportRequestState.FINISHED* or *BulkImportRequestState.FAILED*, periodically refreshing object's state.

Parameters `sleep_time_seconds` (`str`) – a time to block between subsequent API calls

`labelbox.schema.bulk_import_request.get_mal_schemas(ontology)`

Converts a project ontology to a dict for easier lookup during ndjson validation

Parameters `ontology` (`Ontology`) –

Returns Useful for looking up a tool from a given feature schema id

Return type Dict

`labelbox.schema.bulk_import_request.parse_classification(tool)`

Parses a classification from an ontology. Only radio, checklist, and text are supported for mal

Parameters `tool` (`dict`) –

Returns dict

DATAROW

```
class labelbox.schema.data_row.Datarow(*args, **kwargs)
Bases: labelbox.orm.db_object.DbObject, labelbox.orm.db_object.Updateable,
labelbox.orm.db_object.BulkDeletable

Internal Labelbox representation of a single piece of data (e.g. image, video, text).

external_id
User-generated file name or identifier
    Type str

row_data
Paths to local files are uploaded to Labelbox's server. Otherwise, it's treated as an external URL.
    Type str

updated_at
    Type datetime

created_at
    Type datetime

media_attributes
generated media attributes for the datarow
    Type dict

dataset
    ToOne relationship to Dataset
    Type Relationship

created_by
    ToOne relationship to User
    Type Relationship

organization
    ToOne relationship to Organization
    Type Relationship

labels
   ToMany relationship to Label
    Type Relationship

attachments
```

Type Relationship

static bulk_delete(data_rows)
Deletes all the given DataRows.

Parameters `data_rows` (*list of DataRow*) – The DataRows to delete.

create_attachment(attachment_type, attachment_value)

Adds an AssetAttachment to a DataRow. Labelers can view these attachments while labeling.

```
>>> datarow.create_attachment("TEXT", "This is a text message")
```

Parameters

- **attachment_type** (*str*) – Asset attachment type, must be one of: VIDEO, IMAGE, TEXT, IMAGE_OVERLAY (AssetAttachment.AttachmentType)
- **attachment_value** (*str*) – Asset attachment value.

Returns AssetAttachment DB object.

Raises `ValueError` – asset_type must be one of the supported types.

**CHAPTER
SIX**

DATASET

```
class labelbox.schema.dataset.Dataset (client, field_values)
Bases: labelbox.orm.db_object.DbObject, labelbox.orm.db_object.Updateable,
labelbox.orm.db_object.Deletable

A Dataset is a collection of DataRows.

name
    Type str

description
    Type str

updated_at
    Type datetime

created_at
    Type datetime

row_count
    The number of rows in the dataset. Fetch the dataset again to update since this is cached.
    Type int

projects
    ToMany relationship to Project
    Type Relationship

data_rows
    ToMany relationship to DataRow
    Type Relationship

created_by
   ToOne relationship to User
    Type Relationship

organization
    ToOne relationship to Organization
    Type Relationship

create_data_row (**kwargs)
    Creates a single DataRow belonging to this dataset.
```

```
>>> dataset.create_data_row(row_data="http://my_site.com/photos/img_01.jpg")
```

Parameters `**kwargs` – Key-value arguments containing new *DataRow* data. At a minimum, must contain `row_data`.

Raises

- `InvalidQueryError` – If `DataRow.row_data` field value is not provided in `kwargs`.
- `InvalidAttributeError` – in case the DB object type does not contain any of the field names given in `kwargs`.

create_data_rows (`items`)

Asynchronously bulk upload data rows

Use this instead of `Dataset.create_data_rows_sync` uploads for batches that contain more than 1000 data rows.

Parameters `items` (*iterable of (dict or str)*) – See the docstring for `Dataset._create_descriptor_file` for more information

Returns Task representing the data import on the server side. The Task can be used for inspecting task progress and waiting until it's done.

Raises

- `InvalidQueryError` – If the `items` parameter does not conform to the specification above or if the server did not accept the `DataRow` creation request (unknown reason).
- `ResourceNotFoundError` – If unable to retrieve the Task for the import process. This could imply that the import failed.
- `InvalidAttributeError` – If there are fields in `items` not valid for a `DataRow`.
- `ValueError` – When the upload parameters are invalid

create_data_rows_sync (`items`)

Synchronously bulk upload data rows.

Use this instead of `Dataset.create_data_rows` for smaller batches of data rows that need to be uploaded quickly. Cannot use this for uploads containing more than 1000 data rows. Each data row is also limited to 5 attachments.

Parameters `items` (*iterable of (dict or str)*) – See the docstring for `Dataset._create_descriptor_file` for more information.

Returns None. If the function doesn't raise an exception then the import was successful.

Raises

- `InvalidQueryError` – If the `items` parameter does not conform to the specification in `Dataset._create_descriptor_file` or if the server did not accept the `DataRow` creation request (unknown reason).
- `InvalidAttributeError` – If there are fields in `items` not valid for a `DataRow`.
- `ValueError` – When the upload parameters are invalid

data_row_for_external_id (`external_id`)

Convenience method for getting a single `DataRow` belonging to this `Dataset` that has the given `external_id`.

Parameters `external_id` (`str`) – External ID of the sought `DataRow`.

Returns A single `DataRow` with the given ID.

Raises `labelbox.exceptions.ResourceNotFoundError` – If there is no *DataRow* in this *DataSet* with the given external ID, or if there are multiple *DataRows* for it.

data_rows_for_external_id(*external_id*, *limit*=10)

Convenience method for getting a single *DataRow* belonging to this *Dataset* that has the given *external_id*.

Parameters

- **external_id**(*str*) – External ID of the sought *DataRow*.
- **limit**(*int*) – The maximum number of data rows to return for the given *external_id*

Returns A single *DataRow* with the given ID.

Raises `labelbox.exceptions.ResourceNotFoundError` – If there is no *DataRow* in this *DataSet* with the given external ID, or if there are multiple *DataRows* for it.

export_data_rows(*timeout_seconds*=120)

Returns a generator that produces all data rows that are currently attached to this dataset.

Parameters **timeout_seconds**(*float*) – Max waiting time, in seconds.

Returns Generator that yields *DataRow* objects belonging to this dataset.

Raises `LabelboxError` – if the export fails or is unable to download within the specified time.

CHAPTER
SEVEN

LABEL

```
class labelbox.schema.label.Label(*args, **kwargs)
Bases:    labelbox.orm.db_object.DbObject,  labelbox.orm.db_object.Updateable,
          labelbox.orm.db_object.BulkDeletable

Label represents an assessment on a DataRow. For example one label could contain 100 bounding boxes (annotations).

label
      Type str
seconds_to_label
      Type float
agreement
      Type float
benchmark_agreement
      Type float
is_benchmark_reference
      Type bool
project
      ToOne relationship to Project
      Type Relationship
data_row
      ToOne relationship to DataRow
      Type Relationship
reviews
     ToMany relationship to Review
      Type Relationship
created_by
      ToOne relationship to User
      Type Relationship
static bulk_delete(labels)
    Deletes all the given Labels.

    Parameters labels (list of Label) – The Labels to delete.
```

create_benchmark()

Creates a Benchmark for this Label.

Returns The newly created Benchmark.

create_review(kwargs)**

Creates a Review for this label.

Parameters ****kwargs** – Review attributes. At a minimum, a *Review.score* field value must be provided.

CHAPTER
EIGHT

LABELINGFRONTEND

```
class labelbox.schema.labeling_frontend.LabelingFrontend(client, field_values)
Bases: labelbox.orm.db_object.DbObject
```

Label editor.

Represents an HTML / JavaScript UI that is used to generate labels. “Editor” is the default Labeling Frontend that comes in every organization. You can create new labeling frontends for an organization.

name

Type str

description

Type str

iframe_url_path

Type str

projects

ToMany relationship to Project

Type Relationship

LABELINGFRONTENDOPTIONS

```
class labelbox.schema.labeling_frontend.LabelingFrontendOptions(client,
                                                               field_values)
Bases: labelbox.orm.db_object.DbObject
Label interface options.

customization_options
    Type str

project
    ToOne relationship to Project
        Type Relationship

labeling_frontend
    ToOne relationship to LabelingFrontend
        Type Relationship

organization
    ToOne relationship to Organization
        Type Relationship
```


LABELINGPARAMETER OVERRIDE

```
class labelbox.schema.project.LabelingParameterOverride(client, field_values)  
Bases: labelbox.orm.db_object.DbObject
```

Customizes the order of assets in the label queue.

priority

A prioritization score.

Type int

number_of_labels

Number of times an asset should be labeled.

Type int

CHAPTER
ELEVEN

ONTOLOGY

```
labelbox.schema.ontology.FeatureSchemaId
    alias of labelbox.schema.ontology.ConstrainedStrValue

class labelbox.schema.ontology.Ontology(*args, **kwargs)
    Bases: labelbox.orm.db_object.DbObject

    An ontology specifies which tools and classifications are available to a project. This is read only for now. ...
    attribute:: name

        type str

    description
        Type str

    updated_at
        Type datetime

    created_at
        Type datetime

    normalized
        Type json

    object_schema_count
        Type int

    classification_schema_count
        Type int

    projects
        ToMany relationship to Project
        Type Relationship

    created_by
       ToOne relationship to User
        Type Relationship

    classifications () → List[labelbox.schema.ontology.Classification]
        Get list of classifications in an Ontology.

    tools () → List[labelbox.schema.ontology.Tool]
        Get list of tools (AKA objects) in an Ontology.
```

```
class labelbox.schema.ontology.OntologyBuilder(tools: List[labelbox.schema.ontology.Tool]
                                              = <factory>, classifications:
                                              List[labelbox.schema.ontology.Classification]
                                              = <factory>)
```

Bases: object

A class to help create an ontology for a Project. This should be used for making Project ontologies from scratch. OntologyBuilder can also pull from an already existing Project's ontology.

There are no required instantiation arguments.

To create an ontology, use the asdict() method after fully building your ontology within this class, and inserting it into project.setup() as the “labeling_frontend_options” parameter.

Example

```
builder = OntologyBuilder() ... frontend = list(client.get_labeling_frontends())[0] project.setup(frontend,
builder.asdict())

tools
(list)

classifications
(list)

labelbox.schema.ontology.SchemaId
alias of labelbox.schema.ontology.ConstrainedStrValue
```

CHAPTER
TWELVE

ORGANIZATION

```
class labelbox.schema.organization.Organization(*args, **kwargs)
Bases: labelbox.orm.db_object.DbObject

An Organization is a group of Users.

It is associated with data created by Users within that Organization. Typically all Users within an Organization have access to data created by any User in the same Organization.

updated_at
    Type datetime

created_at
    Type datetime

name
    Type str

users
    ToMany relationship to User
    Type Relationship

projects
    ToMany relationship to Project
    Type Relationship

webhooks
    ToMany relationship to Webhook
    Type Relationship

get_default_iam_integration()
    Returns the default IAM integration for the organization. Will return None if there are no default integrations for the org.

get_iam_integrations()
    Returns all IAM Integrations for an organization

invite_limit() → labelbox.schema.invite.InviteLimit
    Retrieve invite limits for the org This already accounts for users currently in the org Meaning that used = users + invites, remaining = limit - (users + invites)

    Returns InviteLimit
```

```
invite_user (email: str, role: labelbox.schema.role.Role, project_roles: Optional[List[labelbox.schema.role.ProjectRole]] = None) → labelbox.schema.invite.Invite
```

Invite a new member to the org. This will send the user an email invite

Parameters

- **email** (`str`) – email address of the user to invite
- **role** (`Role`) – Role to assign to the user
- **project_roles** (`Optional[List[ProjectRoles]]`) – List of project roles to assign to the User (if they have a project based org role).

Returns Invite for the user

Notes

This function is currently experimental and has a few limitations that will be resolved in future releases 1. If you try to add an unsupported you will get an error referring to invalid foreign keys

- In this case `role.get_roles` is likely not getting the right ids
2. **Multiple invites can be sent for the same email. This can only be resolved in the UI for now.**
 - Future releases of the SDK will support the ability to query and revoke invites to solve this problem (and/or checking on the backend)
 3. Some server side response are unclear (e.g. if the user invites themselves `None` is returned which the SDK raises as a `LabelboxError`)

```
remove_user (user: labelbox.schema.user.User)
```

Deletes a user from the organization. This cannot be undone without sending another invite.

Parameters `user` (`User`) – The user to delete from the org

CHAPTER
THIRTEEN

PROJECT

```
class labelbox.schema.project.Project (client, field_values)
Bases:    labelbox.orm.db_object.DbObject,  labelbox.orm.db_object.Updateable,
          labelbox.orm.db_object.Deletable

A Project is a container that includes a labeling frontend, an ontology, datasets and labels.

name
    Type str

description
    Type str

updated_at
    Type datetime

created_at
    Type datetime

setup_complete
    Type datetime

last_activity_time
    Type datetime

auto_audit_number_of_labels
    Type int

auto_audit_percentage
    Type float

datasets
    ToMany relationship to Dataset
    Type Relationship

created_by
   ToOne relationship to User
    Type Relationship

organization
   ToOne relationship to Organization
    Type Relationship
```

reviews

ToMany relationship to Review

Type Relationship

labeling_frontend

ToOne relationship to LabelingFrontend

Type Relationship

labeling_frontend_options

ToMany relationship to LabelingFrontendOptions

Type Relationship

labeling_parameter_overrides

ToMany relationship to LabelingParameterOverride

Type Relationship

webhooks

ToMany relationship to Webhook

Type Relationship

benchmarks

ToMany relationship to Benchmark

Type Relationship

ontology

ToOne relationship to Ontology

Type Relationship

bulk_import_requests()

Returns bulk import request objects which are used in model-assisted labeling. These are returned with the oldest first, and most recent last.

enable_model_assisted_labeling(toggle: bool = True) → bool

Turns model assisted labeling either on or off based on input

Parameters `toggle` (`bool`) – True or False boolean

Returns True if toggled on or False if toggled off

export_issues(status=None)

Calls the server-side Issues exporting that returns the URL to that payload.

Parameters `status` (`string`) – valid values: Open, Resolved

Returns URL of the data file with this Project's issues.

export_labels(download=False, timeout_seconds=600)

Calls the server-side Label exporting that generates a JSON payload, and returns the URL to that payload.

Will only generate a new URL at a max frequency of 30 min.

Parameters `timeout_seconds` (`float`) – Max waiting time, in seconds.

Returns URL of the data file with this Project's labels. If the server didn't generate during the `timeout_seconds` period, None is returned.

export_queued_data_rows(timeout_seconds=120)

Returns all data rows that are currently enqueued for this project.

Parameters `timeout_seconds` (`float`) – Max waiting time, in seconds.

Returns Data row fields for all data rows in the queue as json

Raises `LabelboxError` – if the export fails or is unable to download within the specified time.

`extend_reservations(queue_type)`

Extends all the current reservations for the current user on the given queue type. :param queue_type: Either “LabelingQueue” or “ReviewQueue” :type queue_type: str

Returns int, the number of reservations that were extended.

`label_generator(timeout_seconds=600)`

Download text and image annotations

Returns LabelGenerator for accessing labels for each text or image

`labeler_performance()`

Returns the labeler performances for this Project.

Returns A PaginatedCollection of LabelerPerformance objects.

`labels(datasets=None, order_by=None)`

Custom relationship expansion method to support limited filtering.

Parameters

- `datasets` (*iterable of Dataset*) – Optional collection of Datasets whose Labels are sought. If not provided, all Labels in this Project are returned.
- `order_by` (*None or (Field, Field.Order)*) – Ordering clause.

`members()`

Fetch all current members for this project

Returns A `PaginatedCollection of `ProjectMember`'s

`review_metrics(net_score)`

Returns this Project's review metrics.

Parameters `net_score` (*None or Review.NetScore*) – Indicates desired metric.

Returns int, aggregation count of reviews for given `net_score`.

`set_labeling_parameter_overrides(data)`

Adds labeling parameter overrides to this project.

See information on priority here: <https://docs.labelbox.com/en/configure-editor/queue-system#reservation-system>

```
>>> project.set_labeling_parameter_overrides([
>>>     (data_row_1, 2, 3), (data_row_2, 1, 4)])
```

Parameters `data` (*iterable*) – An iterable of tuples. Each tuple must contain (DataRow, priority<int>, number_of_labels<int>) for the new override.

Priority:

- **Data will be labeled in priority order.**

- A lower number priority is labeled first.

- Minimum priority is 1.

- **Priority is not the queue position.**

- The position is determined by the relative priority.

- E.g. `[(data_row_1, 5,1), (data_row_2, 2,1), (data_row_3, 10,1)]` will be assigned in the following order: `[data_row_2, data_row_1, data_row_3]`
- Datarows with parameter overrides will appear before datarows without overrides.
- **The priority only effects items in the queue.**
 - Assigning a priority will not automatically add the item back into the queue.

Number of labels:

- **The number of times a data row should be labeled.**
 - Creates duplicate data rows in a project (one for each number of labels).
- **New duplicated data rows will be added to the queue.**
 - Already labeled duplicates will not be sent back to the queue.
- **The queue will never assign the same datarow to a single labeler more than once.**
 - If the number of labels is greater than the number of labelers working on a project then the extra items will remain in the queue (this can be fixed by removing the override at any time).
- Setting this to 1 will result in the default behavior (no duplicates).

Returns bool, indicates if the operation was a success.

setup (*labeling_frontend*, *labeling_frontend_options*)

Finalizes the Project setup.

Parameters

- **labeling_frontend** (`LabelingFrontend`) – Which UI to use to label the data.
- **labeling_frontend_options** (`dict` or `str`) – Labeling frontend options, a.k.a. project ontology. If given a `dict` it will be converted to `str` using `json.dumps`.

unset_labeling_parameter_overrides (*data_rows*)

Removes labeling parameter overrides to this project.

- This will remove unlabeled duplicates in the queue.

Parameters `data_rows` (*iterable*) – An iterable of DataRows.

Returns bool, indicates if the operation was a success.

upload_annotations (*name*: str, *annotations*: Union[str, `pathlib.Path`, Iterable[`Dict`]], *validate*: bool = True) → `labelbox.schema.bulk_import_request.BulkImportRequest`

Uploads annotations to a new Editor project.

Parameters

- **name** (str) – name of the BulkImportRequest job
- **annotations** (str or Path or Iterable) – url that is publicly accessible by Labelbox containing an ndjson file OR local path to an ndjson file OR iterable of annotation rows
- **validate** (bool) – Whether or not to validate the payload before uploading.

Returns BulkImportRequest

upsert_instructions (*instructions_file*: str)

- Uploads instructions to the UI. Running more than once will replace the instructions

Parameters `instructions_file` (`str`) – Path to a local file. * Must be either a pdf, text, or html file.

Raises `ValueError` –

- project must be setup * instructions file must end with one of “.text”, “.txt”, “.pdf”, “.html”

`upsert_review_queue` (`quota_factor`)

Sets the the proportion of total assets in a project to review.

More information can be found here: <https://docs.labelbox.com/en/quality-assurance/review-labels#configure-review-percentage>

Parameters `quota_factor` (`float`) – Which part (percentage) of the queue to reinitiate. Between 0 and 1.

`video_label_generator` (`timeout_seconds=600`)

Download video annotations

Returns LabelGenerator for accessing labels for each video

class `labelbox.schema.project.ProjectMember` (`client, field_values`)

Bases: `labelbox.orm.db_object.DbObject`

CHAPTER
FOURTEEN

REVIEW

```
class labelbox.schema.review.Review(client,field_values)
Bases:    labelbox.orm.db_object.DbObject,    labelbox.orm.db_object.Deletable,
labelbox.orm.db_object.Updateable

Reviewing labeled data is a collaborative quality assurance technique.

A Review object indicates the quality of the assigned Label. The aggregated review numbers can be obtained on a Project object.

created_at
    Type datetime

updated_at
    Type datetime

score
    Type float

created_by
   ToOne relationship to User
    Type Relationship

organization
   ToOne relationship to Organization
    Type Relationship

project
   ToOne relationship to Project
    Type Relationship

label
   ToOne relationship to Label
    Type Relationship

class NetScore(value)
Bases: enum.Enum

Negative, Zero, or Positive.
```

CHAPTER
FIFTEEN

TASK

```
class labelbox.schema.task.Task (client, field_values)
Bases: labelbox.orm.db_object.DbObject
```

Represents a server-side process that might take a longer time to process. Allows the Task state to be updated and checked on the client side.

updated_at

Type datetime

created_at

Type datetime

name

Type str

status

Type str

completion_percentage

Type float

created_by

ToOne relationship to User

Type Relationship

organization

ToOne relationship to Organization

Type Relationship

refresh()

Refreshes Task data from the server.

wait_till_done (timeout_seconds=300)

Waits until the task is completed. Periodically queries the server to update the task attributes.

Parameters **timeout_seconds** (*float*) – Maximum time this method can block, in seconds. Defaults to one minute.

CHAPTER
SIXTEEN

USER

```
class labelbox.schema.user.User (client, field_values)
Bases: labelbox.orm.db_object.DbObject
```

A User is a registered Labelbox user (for example you) associated with data they create or import and an Organization they belong to.

updated_at
Type datetime

created_at
Type datetime

email
Type str

name
Type str

nickname
Type str

intercom_hash
Type str

picture
Type str

is_viewer
Type bool

is_external_viewer
Type bool

organization
ToOne relationship to Organization
Type Relationship

created_tasks
ToMany relationship to Task
Type Relationship

projects
ToMany relationship to Project
Type Relationship

remove_from_project (project: labelbox.schema.project.Project)
Removes a User from a project. Only used for project based users. Project based user means their org role is “NONE”

Parameters `project` ([Project](#)) – Project to remove user from

`update_org_role` (`role: labelbox.schema.role.Role`)

Updated the `User`'s organization role.

See `client.get_roles()` to get all valid roles If you a user is converted from project level permissions to org level permissions and then convert back, their permissions will remain for each individual project

Parameters `role` ([Role](#)) – The role that you want to set for this user.

`upsert_project_role` (`project: labelbox.schema.project.Project, role: labelbox.schema.role.Role`)

Updates or replaces a User's role in a project.

Parameters

- `project` ([Project](#)) – The project to update the users permissions for
- `role` ([Role](#)) – The role to assign to this user in this project.

CHAPTER
SEVENTEEN

WEBHOOK

```
class labelbox.schema.webhook.Webhook (client, field_values)
Bases: labelbox.orm.db_object.DbObject, labelbox.orm.db_object.Updateable

Represents a server-side rule for sending notifications to a web-server whenever one of several predefined actions happens within a context of a Project or an Organization.

updated_at
    Type datetime

created_at
    Type datetime

url
    Type str

topics
    LABEL_CREATED, LABEL_UPDATED, LABEL_DELETED    REVIEW_CREATED, REVIEW_UPDATED, REVIEW_DELETED
    Type str

status
    ACTIVE, INACTIVE, REVOKED
    Type str

class Status (value)
Bases: enum.Enum

An enumeration.

class Topic (value)
Bases: enum.Enum

An enumeration.

static create (client, topics, url, secret, project)
Creates a Webhook.

Parameters
    • client (Client) – The Labelbox client used to connect to the server.
    • topics (list of str) – A list of topics this Webhook should get notifications for. Must be one of Webhook.Topic
    • url (str) – The URL to which notifications should be sent by the Labelbox server.
    • secret (str) – A secret key used for signing notifications.
```

- **project** (`Project or None`) – The project for which notifications should be sent. If None notifications are sent for all events in your organization.

Returns A newly created Webhook.

Raises `ValueError` – If the topic is not one of Topic or status is not one of Status

Information on configuring your server can be found here (this is where the url points to and the secret is set).

<https://docs.labelbox.com/en/configure-editor/webhooks-setup#setup-steps>

delete()

Deletes the webhook

update (`topics=None, url=None, status=None`)

Updates the Webhook.

Parameters

- **topics** (`Optional[List[Topic]]`) – The new topics.
- **Optional[str]** (`url`) – The new URL value.
- **status** (`Optional[Status]`) – The new status. If an argument is set to None then no updates will be made to that field.

CHAPTER
EIGHTEEN

EXCEPTIONS

```
exception labelbox.exceptions.ApiLimitError(message, cause=None)
Bases: labelbox.exceptions.LabelboxError
```

Raised when the user performs too many requests in a short period of time.

```
exception labelbox.exceptions.AuthenticationError(message, cause=None)
Bases: labelbox.exceptions.LabelboxError
```

Raised when an API key fails authentication.

```
exception labelbox.exceptions.AuthorizationError(message, cause=None)
Bases: labelbox.exceptions.LabelboxError
```

Raised when a user is unauthorized to perform the given request.

```
exception labelbox.exceptions.InconsistentOntologyException
Bases: Exception
```

```
exception labelbox.exceptions.InternalServerError(message, cause=None)
Bases: labelbox.exceptions.LabelboxError
```

Nondescript prisma or 502 related errors.

Meant to be retryable.

TODO: these errors need better messages from platform

```
exception labelbox.exceptions.InvalidAttributeError(db_object_type, field)
Bases: labelbox.exceptions.LabelboxError
```

Raised when a field (name or Field instance) is not valid or found for a specific DB object type.

```
exception labelbox.exceptions.InvalidQueryError(message, cause=None)
Bases: labelbox.exceptions.LabelboxError
```

Indicates a malconstructed or unsupported query (either by GraphQL in general or by Labelbox specifically). This can be the result of either client or server side query validation.

```
exception labelbox.exceptions.LabelboxError(message, cause=None)
Bases: Exception
```

Base class for exceptions.

```
exception labelbox.exceptions.MALValidationException(message, cause=None)
Bases: labelbox.exceptions.LabelboxError
```

Raised when user input is invalid for MAL imports.

```
exception labelbox.exceptions.MalformedQueryException
Bases: Exception
```

Raised when the user submits a malformed query.

```
exception labelbox.exceptions.NetworkError(cause)
    Bases: labelbox.exceptions.LabelboxError
```

Raised when an HTTPError occurs.

```
exception labelbox.exceptions.ResourceNotFoundError(db_object_type, params)
    Bases: labelbox.exceptions.LabelboxError
```

Exception raised when a given resource is not found.

```
exception labelbox.exceptions.TimeoutError(message, cause=None)
    Bases: labelbox.exceptions.LabelboxError
```

Raised when a request times-out.

```
exception labelbox.exceptions.UuidError(message, cause=None)
    Bases: labelbox.exceptions.LabelboxError
```

Raised when there are repeat Uuid's in bulk import request.

```
exception labelbox.exceptions.ValidationError(message, cause=None)
    Bases: labelbox.exceptions.LabelboxError
```

Exception raised for when a GraphQL query fails validation (query cost, etc.) E.g. a query that is too expensive, or depth is too deep.

PAGINATION

```
class labelbox.pagination.PaginatedCollection(client: Client, query: str, params: Dict[str, str], dereferencing: Dict[str, Any], obj_class: Type[DbObject], cursor_path: Optional[Dict[str, Any]] = None, experimental: bool = False)
```

Bases: object

An iterable collection of database objects (Projects, Labels, etc...).

Implements automatic (transparent to the user) paginated fetching during iteration. Intended for use by library internals and not by the end user. For a list of attributes see `__init__(...)` documentation. The params of `__init__` map exactly to object attributes.

```
__init__(client: Client, query: str, params: Dict[str, str], dereferencing: Dict[str, Any], obj_class: Type[DbObject], cursor_path: Optional[Dict[str, Any]] = None, experimental: bool = False)
```

Creates a PaginatedCollection.

Parameters

- **client** (`labelbox.Client`) – the client used for fetching data from DB.
- **query** (`str`) – Base query used for pagination. It must contain two ‘%d’ placeholders, the first for pagination ‘skip’ clause and the second for the ‘first’ clause.
- **params** (`dict`) – Query parameters.
- **dereferencing** (`iterable`) – An iterable of `str` defining the keypath that needs to be dereferenced in the query result in order to reach the paginated objects of interest.
- **obj_class** (`type`) – The class of object to be instantiated with each dict containing db values.
- **cursor_path** – If not `None`, this is used to find the cursor
- **experimental** – Used to call experimental endpoints

CHAPTER
TWENTY

ENUMS

class labelbox.schema.enums.**AnnotationImportState** (*value*)

Bases: enum.Enum

State of the import job when importing annotations (RUNNING, FAILED, or FINISHED).

State	Description
RUNNING	Indicates that the import job is not done yet.
FAILED	Indicates the import job failed. Check <i>AnnotationImport.errors</i> for more information
FINISHED	Indicates the import job is no longer running. Check <i>AnnotationImport.statuses</i> for more information

class labelbox.schema.enums.**BulkImportRequestState** (*value*)

Bases: enum.Enum

State of the import job when importing annotations (RUNNING, FAILED, or FINISHED).

If you are not using MEA continue using BulkImportRequest. AnnotationImports are in beta and will change soon.

State	Description
RUNNING	Indicates that the import job is not done yet.
FAILED	Indicates the import job failed. Check <i>BulkImportRequest.errors</i> for more information
FINISHED	Indicates the import job is no longer running. Check <i>BulkImportRequest.statuses</i> for more information

PYTHON MODULE INDEX

|

labelbox.client, 1
labelbox.exceptions, 45
labelbox.pagination, 47
labelbox.schema.asset_attachment, 7
labelbox.schema.benchmark, 9
labelbox.schema.bulk_import_request, 11
labelbox.schema.data_row, 13
labelbox.schema.dataset, 15
labelbox.schema.enums, 49
labelbox.schema.label, 19
labelbox.schema.labeling_frontend, 21
labelbox.schema.ontology, 27
labelbox.schema.organization, 29
labelbox.schema.project, 31
labelbox.schema.review, 37
labelbox.schema.task, 39
labelbox.schema.user, 41
labelbox.schema.webhook, 43

INDEX

Symbols

`__init__()` (*labelbox.client.Client method*), 1
`__init__()` (*labelbox.pagination.PaginatedCollection method*), 47

A

`agreement` (*labelbox.schema.label.Label attribute*), 19
`AnnotationImportState` (*class in labelbox.schema.enums*), 49
`ApiLimitError`, 45
`AssetAttachment` (*class in labelbox.schema.asset_attachment*), 7
`AssetAttachment.AttachmentType` (*class in labelbox.schema.asset_attachment*), 7
`attachment_type` (*labelbox.schema.asset_attachment.AssetAttachment attribute*), 7
`attachment_value` (*labelbox.schema.asset_attachment.AssetAttachment attribute*), 7
`attachments` (*labelbox.schema.data_row.DataRow attribute*), 13
`AuthenticationError`, 45
`AuthorizationError`, 45
`auto_audit_number_of_labels` (*labelbox.schema.project.Project attribute*), 31
`auto_audit_percentage` (*labelbox.schema.project.Project attribute*), 31
`average_agreement` (*labelbox.schema.benchmark.Benchmark attribute*), 9

B

`Benchmark` (*class in labelbox.schema.benchmark*), 9
`benchmark_agreement` (*labelbox.schema.label.Label attribute*), 19
`benchmarks` (*labelbox.schema.project.Project attribute*), 32
`bulk_delete()` (*labelbox.schema.data_row.DataRow static method*), 14

`bulk_delete()` (*labelbox.schema.label.Label static method*), 19
`bulk_import_requests()` (*labelbox.schema.project.Project method*), 32
`BulkImportRequest` (*class in labelbox.schema.bulk_import_request*), 11
`BulkImportRequestState` (*class in labelbox.schema.enums*), 49

C

`classification_schema_count` (*labelbox.schema.ontology.Ontology attribute*), 27
`classifications` (*labelbox.schema.ontology.OntologyBuilder attribute*), 28
`classifications()` (*labelbox.schema.ontology.Ontology method*), 27
`Client` (*class in labelbox.client*), 1
`completed_count` (*labelbox.schema.benchmark.Benchmark attribute*), 9
`completion_percentage` (*labelbox.schema.task.Task attribute*), 39
`create()` (*labelbox.schema.webhook.Webhook static method*), 43
`create_attachment()` (*labelbox.schema.data_row.DataRow method*), 14
`create_benchmark()` (*labelbox.schema.label.Label method*), 19
`create_data_row()` (*labelbox.schema.dataset.Dataset method*), 15
`create_data_rows()` (*labelbox.schema.dataset.Dataset method*), 16
`create_data_rows_sync()` (*labelbox.schema.dataset.Dataset method*), 16
`create_dataset()` (*labelbox.client.Client method*), 1
`create_model()` (*labelbox.client.Client method*), 2
`create_project()` (*labelbox.client.Client method*),

D

- 2**
- create_review()** (*labelbox.schema.label.Label method*), 20
- created_at** (*labelbox.schema.benchmark.Benchmark attribute*), 9
- created_at** (*labelbox.schema.bulk_import_request.BulkImportRequest attribute*), 11
- created_at** (*labelbox.schema.data_row.DataRow attribute*), 13
- created_at** (*labelbox.schema.dataset.Dataset attribute*), 15
- created_at** (*labelbox.schema.ontology.Ontology attribute*), 27
- created_at** (*labelbox.schema.organization.Organization attribute*), 29
- created_at** (*labelbox.schema.project.Project attribute*), 31
- created_at** (*labelbox.schema.review.Review attribute*), 37
- created_at** (*labelbox.schema.task.Task attribute*), 39
- created_at** (*labelbox.schema.user.User attribute*), 41
- created_at** (*labelbox.schema.webhook.Webhook attribute*), 43
- created_by** (*labelbox.schema.benchmark.Benchmark attribute*), 9
- created_by** (*labelbox.schema.bulk_import_request.BulkImportRequest attribute*), 11
- created_by** (*labelbox.schema.data_row.DataRow attribute*), 13
- created_by** (*labelbox.schema.dataset.Dataset attribute*), 15
- created_by** (*labelbox.schema.label.Label attribute*), 19
- created_by** (*labelbox.schema.ontology.Ontology attribute*), 27
- created_by** (*labelbox.schema.project.Project attribute*), 31
- created_by** (*labelbox.schema.review.Review attribute*), 37
- created_by** (*labelbox.schema.task.Task attribute*), 39
- created_tasks** (*labelbox.schema.user.User attribute*), 41
- customization_options** (*labelbox.schema.labeling_frontend.LabelingFrontendOptions attribute*), 23

E

- email** (*labelbox.schema.user.User attribute*), 41
- enable_model_assisted_labeling()** (*labelbox.schema.project.Project method*), 32
- error_file_url** (*labelbox.schema.bulk_import_request.BulkImportRequest attribute*), 11
- errors()** (*labelbox.schema.bulk_import_request.BulkImportRequest property*), 11
- execute()** (*labelbox.client.Client method*), 2
- export_data_rows()** (*labelbox.schema.dataset.Dataset method*), 17
- export_issues()** (*labelbox.schema.project.Project method*), 32
- export_labels()** (*labelbox.schema.project.Project method*), 32
- export_queued_data_rows()** (*labelbox.schema.project.Project method*), 32
- extend_reservations()** (*labelbox.schema.project.Project method*), 33
- external_id** (*labelbox.schema.data_row.DataRow attribute*), 13

F

- FeatureSchemaId** (in module *labelbox.schema.ontology*), 27

G

- get_data_row()** (*labelbox.client.Client method*), 3
- get_data_row_metadata_ontology()** (*labelbox.client.Client method*), 3
- get_dataset()** (*labelbox.client.Client method*), 3
- get_datasets()** (*labelbox.client.Client method*), 3

```

get_default_iam_integration()      (label-    labelbox.exceptions
                                box.schema.organization.Organization
                                module, 45
                                method), 29
get_iam_integrations()           (label-    labelbox.pagination
                                box.schema.organization.Organization
                                module, 47
                                method), 29
get_labeling_frontends()          (label-    labelbox.schema.asset_attachment
                                box.client.Client method), 3
                                module, 7
get_mal_schemas()                (in     labelbox.schema.benchmark
                                module    module, 9
                                box.schema.bulk_import_request), 12
get_model() (labelbox.client.Client method), 3
get_models() (labelbox.client.Client method), 4
get_organization()               (labelbox.client.Client
                                method), 4
get_project() (labelbox.client.Client method), 4
get_projects() (labelbox.client.Client method), 4
get_roles() (labelbox.client.Client method), 4
get_user() (labelbox.client.Client method), 4

|
iframe_url_path                 (label-    labelbox.schema.labeling_frontend
                                box.schema.labeling_frontend.LabelingFrontend
                                module, 21
                                attribute), 21
InconsistentOntologyException, 45
input_file_url                   (label-    labelbox.schema.project
                                box.schema.bulk_import_request.BulkImportRequest
                                module, 31
                                attribute), 11
inputs() (labelbox.schema.bulk_import_request.BulkImportRequest
                                module, 37
                                property), 12
intercom_hash (labelbox.schema.user.User
                                attribute), 41
InternalServerError, 45
InvalidAttributeError, 45
InvalidQueryError, 45
invite_limit()                  (label-    labelbox.schema.webhook
                                box.schema.organization.Organization
                                module, 29
                                method), 29
invite_user()                   (label-    LabelboxError, 45
                                box.schema.organization.Organization
                                module, 29
                                method), 29
is_benchmark_reference         (label-    labeler_performance()
                                box.schema.label.Label attribute), 19
                                (labelbox.schema.project.Project method), 33
is_external_viewer              (label-    labeling_frontend
                                box.schema.user.User
                                attribute), 41
                                (labelbox.schema.labeling_frontend.LabelingFrontendOptions
                                attribute), 23
is_viewer (labelbox.schema.user.User attribute), 41

|
Label (class in labelbox.schema.label), 19
label (labelbox.schema.label.Label attribute), 19
label (labelbox.schema.review.Review attribute), 37
label_generator()               (label-    labeling_frontend
                                box.schema.project.Project method), 33
                                (labelbox.schema.project.Project attribute), 32
labelbox.client
module, 1
                                labeling_frontend_options
                                (labelbox.schema.project.Project attribute), 32
                                labeling_parameter_overrides
                                (labelbox.schema.project.Project attribute), 32
                                labelingFrontend
                                (class in labelbox.schema.labeling_frontend), 21
                                labels (labelbox.schema.data_row.DataRow
                                attribute), 13
                                labels() (labelbox.schema.project.Project method),
                                33
                                last_activity
                                (labelbox.schema.benchmark.Benchmark
                                attribute), 9

```

<p>9 last_activity_time (labelbox.schema.project.Project attribute), 31</p> <p>M</p> <p>MalformedQueryException, 45</p> <p>MALValidationError, 45</p> <p>media_attributes (labelbox.schema.data_row.DataRow attribute), 13</p> <p>members () (labelbox.schema.project.Project method), 33</p> <p>module</p> <ul style="list-style-type: none"> labelbox.client, 1 labelbox.exceptions, 45 labelbox.pagination, 47 labelbox.schema.asset_attachment, 7 labelbox.schema.benchmark, 9 labelbox.schema.bulk_import_request, 11 labelbox.schema.data_row, 13 labelbox.schema.dataset, 15 labelbox.schema.enums, 49 labelbox.schema.label, 19 labelbox.schema.labeling_frontend, 21 labelbox.schema.ontology, 27 labelbox.schema.organization, 29 labelbox.schema.project, 31 labelbox.schema.review, 37 labelbox.schema.task, 39 labelbox.schema.user, 41 labelbox.schema.webhook, 43 <p>N</p> <p>name (labelbox.schema.bulk_import_request.BulkImportRequest attribute), 11</p> <p>name (labelbox.schema.dataset.Dataset attribute), 15</p> <p>name (labelbox.schema.labeling_frontend.LabelingFrontend attribute), 21</p> <p>name (labelbox.schema.organization.Organization attribute), 29</p> <p>name (labelbox.schema.project.Project attribute), 31</p> <p>name (labelbox.schema.task.Task attribute), 39</p> <p>name (labelbox.schema.user.User attribute), 41</p> <p>NetworkError, 46</p> <p>nickname (labelbox.schema.user.User attribute), 41</p> <p>normalized (labelbox.schema.ontology.Ontology attribute), 27</p> <p>number_of_labels (labelbox.schema.project.LabelingParameterOverride attribute), 25</p>	<p>O</p> <p>object_schema_count (labelbox.schema.ontology.Ontology attribute), 27</p> <p>Ontology (class in labelbox.schema.ontology), 27</p> <p>ontology (labelbox.schema.project.Project attribute), 32</p> <p>OntologyBuilder (class in labelbox.schema.ontology), 27</p> <p>Organization (class in labelbox.schema.organization), 29</p> <p>organization (labelbox.schema.data_row.DataRow attribute), 13</p> <p>organization (labelbox.schema.dataset.Dataset attribute), 15</p> <p>organization (labelbox.schema.labeling_frontend.LabelingFrontendOptions attribute), 23</p> <p>organization (labelbox.schema.project.Project attribute), 31</p> <p>organization (labelbox.schema.review.Review attribute), 37</p> <p>organization (labelbox.schema.task.Task attribute), 39</p> <p>organization (labelbox.schema.user.User attribute), 41</p> <p>P</p> <p>PaginatedCollection (class in labelbox.pagination), 47</p> <p>parse_classification () (in module labelbox.schema.bulk_import_request), 12</p> <p>picture (labelbox.schema.user.User attribute), 41</p> <p>priority (labelbox.schema.project.LabelingParameterOverride attribute), 25</p> <p>project (class in labelbox.schema.project), 31</p> <p>project (labelbox.schema.bulk_import_request.BulkImportRequest attribute), 11</p> <p>project (labelbox.schema.label.Label attribute), 19</p> <p>project (labelbox.schema.labeling_frontend.LabelingFrontendOptions attribute), 23</p> <p>project (labelbox.schema.review.Review attribute), 37</p> <p>ProjectMember (class in labelbox.schema.project), 35</p> <p>projects (labelbox.schema.dataset.Dataset attribute), 15</p> <p>projects (labelbox.schema.labeling_frontend.LabelingFrontend attribute), 21</p> <p>projects (labelbox.schema.ontology.Ontology attribute), 27</p> <p>projects (labelbox.schema.organization.Organization attribute), 29</p> <p>projects (labelbox.schema.user.User attribute), 41</p>
--	---

R

reference_label (labelbox.schema.benchmark.Benchmark attribute), 9
 refresh() (labelbox.schema.bulk_import_request.BulkImportRequest method), 12
 refresh() (labelbox.schema.task.Task method), 39
 remove_from_project() (labelbox.schema.user.User method), 41
 remove_user() (labelbox.schema.organization.Organization method), 30
 ResourceNotFoundError, 46
 Review (class in labelbox.schema.review), 37
 Review.NetScore (class in labelbox.schema.review), 37
 review_metrics() (labelbox.schema.project.Project method), 33
 reviews (labelbox.schema.label.Label attribute), 19
 reviews (labelbox.schema.project.Project attribute), 31
 row_count (labelbox.schema.dataset.Dataset attribute), 15
 row_data (labelbox.schema.data_row.DataRow attribute), 13

S

SchemaId (in module labelbox.schema.ontology), 28
 score (labelbox.schema.review.Review attribute), 37
 seconds_to_label (labelbox.schema.label.Label attribute), 19
 set_labeling_parameter_overrides() (labelbox.schema.project.Project method), 33
 setup() (labelbox.schema.project.Project method), 34
 setup_complete (labelbox.schema.project.Project attribute), 31
 state (labelbox.schema.bulk_import_request.BulkImportRequest attribute), 11
 status (labelbox.schema.task.Task attribute), 39
 status (labelbox.schema.webhook.Webhook attribute), 43
 status_file_url (labelbox.schema.bulk_import_request.BulkImportRequest attribute), 11
 statuses() (labelbox.schema.bulk_import_request.BulkImportRequest property), 12

T

Task (class in labelbox.schema.task), 39
 TimeoutError, 46
 tools (labelbox.schema.ontology.OntologyBuilder attribute), 28
 tools() (labelbox.schema.ontology.Ontology method), 27

topics (labelbox.schema.webhook.Webhook attribute), 43

U

import_labeling_parameter_overrides() (labelbox.schema.project.Project method), 34
 update() (labelbox.schema.webhook.Webhook method), 44
 update_org_role() (labelbox.schema.user.User method), 42
 updated_at (labelbox.schema.data_row.DataRow attribute), 13
 updated_at (labelbox.schema.dataset.Dataset attribute), 15
 updated_at (labelbox.schema.ontology.Ontology attribute), 27
 updated_at (labelbox.schema.organization.Organization attribute), 29
 updated_at (labelbox.schema.project.Project attribute), 31
 updated_at (labelbox.schema.review.Review attribute), 37
 updated_at (labelbox.schema.task.Task attribute), 39
 updated_at (labelbox.schema.user.User attribute), 41
 updated_at (labelbox.schema.webhook.Webhook attribute), 43

upload_annotations() (labelbox.schema.project.Project method), 34

upsert_instructions() (labelbox.schema.project.Project method), 34

upsert_project_role() (labelbox.schema.user.User method), 42

upsert_review_queue() (labelbox.schema.project.Project method), 35

url (labelbox.schema.webhook.Webhook attribute), 43

User (class in labelbox.schema.user), 41

users (labelbox.schema.organization.Organization attribute), 29

UuidError, 46

V

ValidationFailedError, 46

video_label_generator() (labelbox.schema.project.Project method), 35

W

wait_till_done() (labelbox.schema.task.Task method), 39

wait_until_done() (labelbox.schema.bulk_import_request.BulkImportRequest method), 12

Webhook (class in labelbox.schema.webhook), 43

Webhook.Status (class in labelbox.schema.webhook), 43

`Webhook.Topic` (*class in labelbox.schema.webhook*),
43
`webhooks` (*labelbox.schema.organization.Organization attribute*), 29
`webhooks` (*labelbox.schema.project.Project attribute*),
32